pure¹¹



Empfohlene Reinraumklassen ISO 5|6|7|8|9 GMP C|D

Tupfer CrushTube Swab #TX726

pure11-Nr.: 1106326, Marke: TexWipe

Eigenschaften

- Marke: TexWipe
- Kopfform: rechteckig
- Material Tupferkopf: Polyester-Vlies
- Material Schaft: Glas
- Grifflänge in mm: 50 mm
- Tränkung
- Selbsttränkend
- Material: Polyester/Glas
- Art des Kopfes: starr
- Kopflänge in mm: 10 mm
- Kopfbreite in mm: 8 mm
- Anzahl in kleinster Unterverpackung: 50
- Ausprägung Kopf: einseitig
- Farbe Griff: Weiß

pure¹¹ GmbH

Bavariafilmplatz 7 | D-82031 Grünwald Geschäftsführung: Julian Kropp, Linda Vereycken, Lars Engeler AG München HRB 171307 T +49 89 5589434 0 F +49 89 5589434 77 www.pure11.de info@pure11.de

pure¹¹

Material

- Polyester/Glas
- Verpackung
- 50STK

Produktvarianten

pure¹¹-Nr.: 1106326, Tupfer CrushTube Swab #TX726

IPA-getränkt; Material: Polyester / VE: 50STK

pure¹¹ GmbH

Bavariafilmplatz 7 | D-82031 Grünwald Geschäftsführung: Julian Kropp, Linda Vereycken, Lars Engeler AG München HRB 171307 T +49 89 5589434 0 F +49 89 5589434 77 www.pure11.de info@pure11.de



Specialty Swabs CrushTube[™] Swab

TECHNICAL DATA SHEET

TX726 CrushTube[™] Swab





Description

Texwipe's CrushTube system includes a 100% polyester (hydroentangled) nonwoven material head attached to an internal vial containing 91% IPA / 9% DIW solution, which is enclosed in a protective casing.

When the internal vial is crushed, the head becomes saturated with the 91% IPA / 9% DIW solution for Point-of–Use application.

Individually packaged in cleanroom compatible material. Lot coded for traceability and quality control.

Features & Benefits

- IPA solution is separated from head until activated
- . Gently crush the vial to release the IPA and saturate the brush/tip
- Precision spot cleaning, no extra container of solvent needed
- Individually packaged to minimize storage need, easy to transport and use

Applications

- Solvent cleaning and maintaining of ion emitter tips
- Cleaning of grooves, tracks, slots and other small spaces
- Removing adhesive buildup
- Solvent cleaning sensitive surfaces such as optical assemblies

Industries

- Automotive
- Biologics
- Food Manufacturing
- Microelectronics
- Pharmaceuticals
- Semiconductor

Products

See reverse for Physical and Contamination Characteristics



Specialty Swabs CrushTube[™] Swab

TECHNICAL DATA SHEET

TX726

Physical Characteristics

	ТХ726
Head material	Polyester
Head width	8.3 mm (0.33")
Head length	10.0 mm (0.39")
Handle material	Ampule with 91% IPA / 9% DIW in a polymer sleeve
Handle width	9.5 mm (0.37")
Handle length	44.0 mm (1.73")
Total swab length	47.6 mm (1.89")
Handle color	Transparent
Design notes	Polyester tip with ampule reservoir of 0.50mL 91% isopropyl alcohol/9% DIW

Directions for Use on Ion Emitter Tips

- 1. Turn off power to the emitter points to be cleaned.
- 2. Peel open the package, remove the CrushTube Swab and discard the package.
- 3. The CrushTube swab has a glass vial of alcohol inside of a plastic tube. Crush the inner glass vial by squeezing the plastic tube, then tip the swab to allow the alcohol to wet the brush.
- 4. Carefully insert the wetted swab end onto the emitter point. Slowly rotate the tube and then withdraw it. Repeat until all visible deposited material has been removed. (Each CrushTube swab can clean 5 to 8 emitter points, depending upon the amount of residue. When the swab fails to remove the residue, a new swab should be used.)
- 5. Clean all emitter points in the ionizer assembly, wait a few moments for the alcohol to evaporate, then apply power to the ionizer assembly.

Products

Number	Description	Packaging
TX726	CrushTube [™] Swab	50 swabs/box; 10 boxes/case

* Testing Method: TM2: Laboratory Testing for Swabs. Test method is available upon request. Values are typical, not representing specification limits.



Before Cleaning



After Cleaning

Texwipe Regulatory Certificates

Texwipe is the only wiper company to be registered: ISO 9001 • ISO 13485 • ISO 14001 • OHSAS 18001



Texwipe[®] Swabs 90-91% IPA

SAFETY DATA SHEET

Section 1. Identification

GHS product identifier	: Texwipe [®] Swabs 90-91% IPA
Product code	: TX726
Product type	: Liquid.

Identified uses

For use in various cleaning applications.

Supplier/Manufacturer	: Texwipe 1210 South Park Drive Kernersville, NC 27284 Tel: 1-(336) 996-7046 (Toll Free: 1-(800) 839-9473) Fax: 1-(336) 996-6563 Web: www.texwipe.com
Emergency telephone number (with hours of operation)	: CHEMTREC, U.S. : 1-800-424-9300 International: +1-703-527-3887

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	 H225 - Highly flammable liquid and vapor. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.
Precautionary statements	
Prevention	 P280 - Wear protective gloves. Wear eye or face protection. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P233 - Keep container tightly closed. P271 - Use only outdoors or in a well-ventilated area. P261 - Avoid breathing vapor. P264 - Wash hands thoroughly after handling.



Section 2. Hazards identification

Response	 P304 + P340 + P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical attention.
Storage	: P405 - Store locked up. P403 - Store in a well-ventilated place. P235 - Keep cool.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture	
Other means of identification	: Not available.	

Ingredient name	%	CAS number
Isopropyl Alcohol	90 - 91	67-63-0

United States: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Canada: The exact percentage (concentration) in the composition has been withheld as a trade secret in accordance with the amended HPR as of April 2018.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	 Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.



Section 4. First aid measures

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Potential acute health effe	<u>cts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	 Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: Can cause central nervous system (CNS) depression.
Over-exposure signs/symp	<u>otoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Indication of immediate med	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Unsuitable extinguishing media	: Do not use water jet or water-based fire extinguishers.



Section 5. Fire-fighting measures

Specific hazards arising from the chemical	: Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.				
For emergency responders	:	f specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".				
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).				
Methods and materials for co	nta	ainment and cleaning up				
Spill	:	Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.				

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.



Section 7. Handling and storage

Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

United States

Occupational exposure limits

Ingredient name	Exposure limits
Isopropyl Alcohol	ACGIH TLV (United States, 3/2017). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. NIOSH REL (United States, 10/2016). TWA: 400 ppm 10 hours. TWA: 980 mg/m³ 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m³ 15 minutes.
	OSHA PEL (United States, 6/2016). TWA: 400 ppm 8 hours. TWA: 980 mg/m ³ 8 hours.

Canada

Occupational exposure limits

Ingredient name	Exposure limits
Ingredient name Isopropyl Alcohol	CA Alberta Provincial (Canada, 4/2009). 15 min OEL: 984 mg/m³ 15 minutes. 8 hrs OEL: 200 ppm 8 hours. 15 min OEL: 400 ppm 15 minutes. 8 hrs OEL: 492 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 7/2016). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. CA Ontario Provincial (Canada, 7/2015). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 400 ppm 8 hours. STEV: 500 ppm 15 minutes. STEV: 500 ppm 15 minutes. STEV: 500 ppm 15 minutes.
	CA Saskatchewan Provincial (Canada, 7/2013). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.



Section 8. Exposure controls/personal protection

Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.		
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.		
Individual protection measur	<u>es</u>		
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.		
Skin protection			
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.		
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.		
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.		
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.		

Section 9. Physical and chemical properties

<u>Appearance</u>	
Physical state	: Liquid.
Color	: Colorless.
Odor	: Alcohol-like. [Strong]
Odor threshold	: Not available.
рН	Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Closed cup: 18°C (64.4°F) [Tagliabue.]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.





Section 9. Physical and chemical properties

Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	1	Not available.
Vapor density	1	Not available.
Relative density	1	Not available.
Solubility	1	Not available.
Partition coefficient: n- octanol/water	:	Not available.
Auto-ignition temperature	1	Not available.
Decomposition temperature	:	Not available.
Viscosity	1	Not available.
Flow time (ISO 2431)	1	Not available.

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl Alcohol	LD50 Dermal LD50 Oral		12800 mg/kg 5000 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isopropyl Alcohol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 mg	-
	Eyes - Moderate irritant	Rabbit	-	10 mg	-
	Eyes - Severe irritant	Rabbit	-	100 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification





Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP		
Isopropyl Alcohol	-	3	-		
Reproductive toxicity There is no data available. Teratogenicity There is no data available. Specific target organ toxicity	y (single ex	posure)			
Name			Category	Target organs	
Isopropyl Alcohol			Category 3	Narcotic effects	
Specific target organ toxicit	y (repeated	<u>exposure)</u>			
There is no data available. <u>Aspiration hazard</u> There is no data available.					
Information on the likely routes of exposure	: Dermal of	contact. Eye	e contact. Inhalation. In	gestion.	
Potential acute health effects					
Eye contact	: Causes	serious eye	irritation.		
Inhalation	 Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. 				
Skin contact	: No know	n significan	t effects or critical haza	ards.	
Ingestion	: Can cause central nervous system (CNS) depression.				
Symptoms related to the physical	sical, chemi	ical and to	xicological characteri	istics	
Eye contact		symptoms ritation	may include the followi		
Inhalation	: Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness				
Skin contact	: No known significant effects or critical hazards.				
Ingestion	: No know	n significan	t effects or critical haza	ards.	
Delayed and immediate effect	ts and also	chronic eff	fects from short and I	ong term exposure	
<u>Short term exposure</u>					
Potential immediate effects	: No know	n significan	t effects or critical haza	ards.	
Potential delayed effects	: No know	n significan	t effects or critical haza	ards.	
<u>Long term exposure</u>					
Potential immediate effects	: No know	n significan	t effects or critical haza	ards.	



Texwipe® Swabs 90-91% IPA

Section 11. Toxicological information

ffects
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.
: No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	5549.5 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
	Acute LC50 1400000 µg/L Marine water	Daphnia - Daphnia magna Crustaceans - Crangon crangon Fish - Rasbora heteromorpha	48 hours 48 hours 96 hours

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Isopropyl Alcohol	0.05	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects	: No known significant effects or critical hazards.
-----------------------	---

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly



Section 13. Disposal considerations

internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
UN number	UN1219	UN1219	UN1219	UN1219
UN proper shipping name	ISOPROPYL ALCOHOL	ISOPROPYL ALCOHOL	ISOPROPYL ALCOHOL	ISOPROPYL ALCOHOL
Transport hazard class(es)	3	3	3	3
Packing group	Ш	11	11	11
Environmental hazards	No.	No.	No.	No.

AERG : 129

Additional information		
DOT Classification	1	Remarks Limited quantity
TDG Classification	:	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). Remarks Limited quantity
IMDG	1	Remarks Limited quantity
ΙΑΤΑ	:	Remarks Limited quantity
Special precautions for user		Transport within user's premises: always transport in closed containers that are

the event of an accident or spillage.

Section 15. Regulatory information

•	•
U.S. Federal regulations	: United State
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List II Chemicals (Essential Chemicals)	: Not listed

: United States inventory (TSCA 8b): All components are listed or exempted.

upright and secure. Ensure that persons transporting the product know what to do in

SARA 302/304

Composition/information on ingredients





Section 15. Regulatory information

No products were found.	
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	: FLAMMABLE LIQU

JIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) -Category 3

Composition/information on ingredients

Name	Classification
	FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

SARA 313

	Product name	CAS number
Form R - Reporting requirements	Isopropyl alcohol	67-63-0
Supplier notification	Isopropyl alcohol	67-63-0

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

State regulations	
Massachusetts	: The following components are listed: Isopropyl Alcohol
New York	: None of the components are listed.
New Jersey	: The following components are listed: Isopropyl Alcohol
Pennsylvania	: The following components are listed: Isopropyl Alcohol
<u>California Prop. 65</u>	
No products were found.	
<u>Canada</u>	
<u>Canadian lists</u>	
Canadian NPRI	: The following components are listed: Isopropyl Alcohol
CEPA Toxic substances	: None of the components are listed.
Canada inventory (DSL NDSL)	: All components are listed or exempted.

Section 16. Other information

Procedure used to derive the classification

Classification		Justification
FLAMMABLE LIQUIDS - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3		On basis of test data Calculation method Calculation method
<u>History</u>		
Date of issue mm/dd/yyyy	: 09/15/2018	
Date of previous issue	: Not applicable	

Ve	rsi	on

: Not applicable

: 1





Section 16. Other information

Prepared by

: KMK Regulatory Services Inc.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.