

Empfohlene Reinraumklassen

ISO 4 | 5 | 6 | 7 | 8 | 9

GMP C | D

Reinraum-Klebeband Polyethylen #1154-1,5

pure[11]-Nr.: 1130040, Marke: UltraTape

Eigenschaften

- Marke: UltraTape
- Material: Polyethylen
- Breite in cm: 3,81 cm
- Beschreibbar
- Länge in m: 32,9
- Anzahl in kleinster Unterverpackung: 32
- Klebestärke: mittel
- Klebstoff: Gummi
- Polyethylen: 100 %
- Reinheitsgrad: Ultra Clean
- Rückstandsfrei ablösbar

we care

pure[11] GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

Material

- Polyethylen

Verpackung

- 4STK

Produktvarianten

pure[11]-Nr.: 1130040WH1_5I, Reinraum-Klebeband Polyethylen #1154-1,5

Farbe: Weiß; Breite: 1,5" / VE: 4STK

pure[11] GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

UltraTape
Adhesive Tape & Labels for Critical Environments

PRODUCT DATASHEET

UT1154 Polyethylene Medium Adhesion Cleanroom Tape

DESCRIPTION

UltraTape 1154/ 0154 medium tack cleanroom tape is ideal for general purpose and construction applications where a strong hold is required. The rubber adhesive bonds quickly to most surfaces and is considered low residue for glass, metal, and plastic.

- Residue free removal from most surfaces
- Easy to tear by hand
- Easy to write on with a pen
- Very low outgassing

PROPERTIES

Backing	Polyethylene
Adhesive	Synthetic Rubber
Elongation	80%
Adhesive Thickness	2.5 mils / 0.064 mm
Total Thickness	7.0 mils / 0.18 mm
Adhesion to Stainless	20 oz/in (5.6 N/25 mm)
Operating Temperature	32°F to 160°F (0°C to 70°C)
Tensile Strength	24 lbs./in (105 N/25 mm)
Length	36 yards
Colors	White (WH)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21C°) with 50% relative humidity.

9770 SW Wilsonville Road, Suite 400
Wilsonville, OR 97070
www.cleanroomtape.com

503.427.2880
503.482.5616

© UltraTape 2022 | Rev. 05/2022

ISO 9001:2015

UL LISTED

A division of DELPHON