

UltraTape



Reinraum-Klebeband PE Surface-Protection #1314-0,5

pure¹¹-Nr.: 1130070, Marke: UltraTape

Eigenschaften

- Marke: UltraTape
- Material: Polyethylen
- Breite in cm: 1,27 cm
- Länge in m: 76,2
- Klebestärke: leicht
- Klebstoff: Acryl
- Reinheitsgrad: Ultra Clean
- Rückstandsfrei ablösbar

Empfohlene

Reinraumklassen

ISO 5|6|7|8|9

GMP C|D

Material

- Polyethylen

Verpackung

- 12STK

Produktvarianten

pure¹¹-Nr.: 1130070TP0_5l, Reinraum-Klebeband PE Surface-Protection #1314-0,5

Farbe: Transparent; Breite: 0,5" / VE: 12STK

UT1314 Polyethylene Low Adhesion Surface Protection Cleanroom Tape

DESCRIPTION

UltraTape 1314/ 0314 cleanroom tape is a low adhesion temporary protection tape designed for a variety of surface protection applications including metal, plastic, and painted surfaces.

- Low Tack surface protection against dust, dirt and moderate abrasion
- Stable adhesion levels resulting in good removability
- Clean removal
- Cleanroom certified

PROPERTIES

Backing	Polyethylene
Adhesive	Acrylic
Total Thickness	3.0 mils / 0.08 mm
Elongation	450%
Adhesion to Stainless Steel	11.0 oz/in (3.02 N/25 mm)
Release Liner	N/A
Operating Temperature	-40°F to 190°F (-40°C to 88°C)
Tensile Strength	2500 PSI
Length	250 ft.
Colors	Clear (CL)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.