

UltraTape



Reinraum-Klebeband Vinyl Antistatisch #0286-2

pure¹¹-Nr.: 1130075, Marke: UltraTape

Eigenschaften

- Marke: UltraTape
- Material: Vinyl
- Breite in cm: 5,08 cm
- Antistatisch
- Beschreibbar
- Anzahl in kleinster Unterverpackung: 1
- Klebstoff: Acryl
- Reinheitsgrad: Classic Clean
- Vinyl: 100 %

Empfohlene

Reinraumklassen

ISO 4|5|6|7|8|9

GMP C|D

Material

- Vinyl

Verpackung

- STK

Produktvarianten

pure¹¹-Nr.: 1130075YL2I, Reinraum-Klebeband Vinyl Antistatisch #0286-2

Farbe: Gelb; Breite: 2" / VE: STK

UT2286 Anti-static Cleanroom Vinyl Marking Tape

DESCRIPTION

UltraTape 2286/ 0286 is a Cleanroom Anti-static tape available in multiple colors for floor, tool and safety marking, as well as a wide range of applications where bright colors are needed.

- Anti-static both sides of the tape
- Bright colors, pen writable
- Solvent resistant
- Excellent durability and abrasion resistance

PROPERTIES

Backing	Vinyl base / PET over lamination / ESD Coated
Adhesive	Acrylic / ESD Coated
Backing Thickness	5.5 mils (0.140mm)
Adhesive Thickness	1 mil (0.025mm)
Adhesion to Stainless	28.8 oz/in (800 g/25mm)
Surface Resistance – Backing Side	$\leq 10E9$
Surface Resistance – Adhesive Side	$\leq 10E9$
Peeling Static Voltage	< 100 V
Elongation	80%
Colors	Blue (BL), Green (GR), Red (RE), White (WH), Yellow (YE)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21C°) with 50% relative humidity.