



Reinraum-Klebeband Double-Sided #1530

pure¹¹-Nr.: 1130104, Marke: UltraTape

Eigenschaften

- Marke: UltraTape
- Breite in cm: 2,54 cm
- Doppelseitig klebend
- Chemikalienbeständigkeit
- Klebestärke: leicht
- Klebstoff: Acryl
- Polyester/PES: 100 %

Empfohlene

Reinraumklassen

ISO 4|5|6|7|8|9

GMP C|D

Material

-

Verpackung

- STK

Produktvarianten

pure¹¹-Nr.: 1130104TP1I, Reinraum-Klebeband Double-Sided #1530

Farbe: Transparent; Breite: 1 Inches / VE: STK

UT1530 Double-Sided Removable Cleanroom Tape with Liner

DESCRIPTION

UltraTape 1530/ 0530 is a removable double sided PVC film tape with acrylic pressure sensitive adhesive on a polypropylene liner for easy cleanroom use.

- Repositionable
- UltraTape Cleanroom certified
- Good resistance to aging and light
- Can be unwound easily, even after long periods in storage

PROPERTIES

Carrier	PVC
Adhesive	Acrylic
Release Liner	Polypropylene
Adhesive Thickness	.0011" per side
Total Tape Thickness	3.4 mils / 0.08636 mm
Elongation	40%
Adhesion to Stainless Steel	22 oz. / in.
Operating Temperature	0°F to 140°F (0°C to 60°C)
Tensile Strength	20 oz. / in.
Colors / Length	Clear (CL) / 36 yards

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.