

UltraTape



Reinraumetiketten Polyethylen Permanent UltraClean

pure¹¹-Nr.: 1130112, Marke: UltraTape

Eigenschaften

- Länge in mm: 101,6 mm
- Breite in mm: 50,8 mm
- Farbe: Weiß
- Marke: UltraTape
- Material: Polyethylen
- Selbsthaftend
- Anzahl Etiketten pro Rolle: 1000
- Durchmesser Rollenkern in inch: 1 In
- Geeignet für Thermotransferdruck

Empfohlene

Reinraumklassen

ISO 5|6|7|8|9

GMP A/B|C|D

Material

- Polyethylen

Verpackung

- 5000STK

Produktvarianten

pure¹¹-Nr.: 1130112, Reinraumetiketten Polyethylen Permanent UltraClean

Farbe: Weiß; Größe: 10,16 x 58 cm (4" x 2") / VE: 5000STK

UTL100 Thermal Transfer Permanent Cleanroom Label Stock

DESCRIPTION

UltraTape 100 is a matte white cleanroom label stock which offers excellent durability, is thermal transfer printable and features a permanent cleanroom acrylic adhesive.

- Thermal transfer printable
- Permanent adhesive
- Cleanroom Certified
- Adheres to a wide variety of substrates

PROPERTIES

Backing	Polypropylene
Adhesive	Acrylic
Release Liner	1.5 mil Clear Polyester
Backing Thickness	2.8 mils
Adhesive Coat Weight	1.75 g/100 in ²
Adhesion to Stainless Steel	3 lbs./in. (528 N/m)
Loop Tack	1.8 lbs./in. (316 N/m)
Operating Temperature	-40°F to 220°F (-40°C to 104°C)
Length	Can be die cut to any custom size
Colors	White (WH) printable to any color

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.