Reinraum-Klebeband Vinyl Antistatisch #2286-2

pure[11]-Nr.: 1130141, Marke: UltraTape

Eigenschaften

- Marke: UltraTape
- Material: Vinyl
- Breite in cm: 5,08 cm
- Antistatisch
- Beschreibbar
- Anzahl in kleinster Unterverpackung: 3
- Klebstoff: Acryl
- Reinheitsgrad: Ultra Clean
- Vinyl: 100 %

Empfohlene Reinraumklassen

ISO 4 | 5 | 6 | 7 | 8 | 9

GMP C | D

pure[11] GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

we care

Material

- Vinyl

Verpackung

- 3STK

Produktvarianten

pure[11]-Nr.: 1130141YL2I, Reinraum-Klebeband Vinyl Antistatisch #2286-2

Farbe: Gelb; Breite: 2 Inches / VE: 3STK

UltraTape
Adhesive Tape & Labels for Critical Environments

PRODUCT DATASHEET

UT2286 Anti-static Cleanroom Vinyl Marking Tape

DESCRIPTION

UltraTape 2286/ 0286 is a Cleanroom Anti-static tape available in multiple colors for floor, tool and safety marking, as well as a wide range of applications where bright colors are needed.

- Anti-static both sides of the tape
- Bright colors, pen writable
- Solvent resistant
- Excellent durability and abrasion resistance

PROPERTIES

Backing	Vinyl base / PET over lamination / ESD Coated
Adhesive	Acrylic / ESD Coated
Backing Thickness	5.5 mils (0.140mm)
Adhesive Thickness	1 mil (0.025mm)
Adhesion to Stainless	28.8 oz/in (800 g/25mm)
Surface Resistance – Backing Side	≤ 10E9
Surface Resistance – Adhesive Side	≤ 10E9
Peeling Static Voltage	< 100 V
Elongation	80%
Colors	Blue (BL), Green (GR), Red (RE), White (WH), Yellow (YE)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.

9770 SW Wilsonville Road, Suite 400
Wilsonville, OR 97070
www.cleanroomtape.com

503.427.2880
503.482.5616

© UltraTape 2022 | Rev. 05/2022

ISO 9001:2015

UL LISTED

A division of DELPHON