

Tuch CELOS Wiper 2.10

pure11-Nr.: 1106239, Marke: CELOS

Eigenschaften

- Steril
- Marke: CELOS
- Flächengewicht in g/m²: 60 g/m²
- Struktur: Vliesstoff
- Material: Polyester/Zellulose
- Lieferform in Verpackung: gelegt
- Verpackungsform: Beutel
- Anzahl in kleinster Unterverpackung: 25
- Kantenverarbeitung: Kalt geschnitten
- Chemikalienbeständigkeit
- Gebrauch: Einweg
- Hydroverfestigt
- Polyester/PES: 50 %
- Sterilisation validiert
- Zellulose: 50 %
- Flächengewicht in g/m²: 60 g/m²

Empfohlene Reinraumklassen

ISO 5 | 6 | 7 | 8 | 9

GMP A/B | C | D

pure11 GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

we care

Material

- Polyester/Zellulose

Verpackung

- 80STK

Produktvarianten

pure[11]-Nr.: 11062391010WH, Tuch CELOS Wiper 2.10

Steril; Größe: 10 x 10 cm (4 x 4"); Farbe: Weiß / VE: 80STK

pure[11]-Nr.: 11062392323WH, Tuch CELOS Wiper 2.10

Steril; Größe: 23 x 23 cm (9 x 9"); Farbe: Weiß / VE: 150STK

pure[11]-Nr.: 11062393131WH, Tuch CELOS Wiper 2.10

Steril; Größe: 31 x 31 cm (12 x 12"); Farbe: Weiß / VE: 150STK

STERILE

CELOS® a pure[11] brand

CELOS® Wiper 2.10

Product information:

Material	Cellulose/Polyester
Process	Non-woven fabric wiper - 50 % virgin cellulose and 50 % polyester fibre
Application	Cleanroom wiper for wet and dry applications, ideal for cleaning, wiping and as soft support
Cutting process	Individual cut
Basic weight	60 g/m² (+/- 5 g)
Thickness	0.23 mm (+/- 0.05 mm)
Color	White

Product:

Part number	*Variant*	*Style*	*Size*	*Inner packaging*	*Outer packaging*	*Quantity per case*
1106239	WH2323	Sterile	23 x 23 cm (9 x 9“)	25 pcs/IB	6 IB/OB	12 OB/case
	WH3131		31 x 31 cm (12 x 12“)	25 pcs/IB	6 IB/OB	10 OB/case

IB=Inner Bag; OB=Outer Bag

Parallel part number 06239	*Please note: The packaging may show either of the parallel valid part numbers during the changeover period.*

Characteristics:

- Mixing process without chemical adhesion, reduces chemical impurities
- High bidirectional strength of material due to hydroentanglement
- Suitable for soft surfaces and sensitives components
- Inspection of every wiper
- Individual cutting of every piece
- Double packaging
- Irradiated by gamma
- Production and packaging in a controlled environment

Performance parameter:

	Specification	*Unit*
Sorbency capacity	> 250	ml/m²
Sorbency (IPA)	< 1	seconds
APC (≥ 0.5 µm)	< 1,200	counts/pcs
LPC (≥ 0.5 µm)	< 8,000	counts/cm²
Extractables NVR (IPA)	< 0.50	mg/g
Cl^-	< 30.0	ppm
SO_4^{2-}	< 40.0	ppm
Minimum irradiation dose	25	kGy
Maximum irradiation dose	50	kGy

pure[11] has made every attempt to ensure the accuracy and reliability of the information provided in this datasheet. However, the information is provided "as is" without warranty of any kind. pure[11] does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained.

we care

pure11 GmbH | Sitz: Grünwald
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de