

CELOS



CELOS®  
a pure<sup>11</sup> brand

## Klebefolienmatte L30-8 CELOS

pure<sup>11</sup>-Nr.: 1108041, Marke: CELOS

### Eigenschaften

- Marke: CELOS
- Breite in cm: 66 cm
- Länge in cm: 114 cm
- Dicke/Stärke der Matte (in mm): 1,5 mm
- Anzahl Lagen: 30
- Abnehmende Indexnummerierung
- Klebestärke: stark
- Farbe: Olivgrün
- Farbe der einzelnen Klebefolien: Blau
- antimikrobiell ausgerüstet

### Empfohlene Reinraumklassen

ISO 4|5|6|7|8|9

GMP C|D

pure<sup>11</sup> GmbH

Bavariafilmplatz 7 | D-82031 Grünwald

Geschäftsführung: Julian Kropp, Linda Vereycken, Lars Engeler

AG München HRB 171307

T +49 89 5589434 0

F +49 89 5589434 77

[www.pure11.de](http://www.pure11.de)

[info@pure11.de](mailto:info@pure11.de)

## Material

- 

## Verpackung

- 8STK

## Produktvarianten

---

**pure<sup>11</sup>-Nr.: 1108041, Klebefolienmatte L30-8 CELOS**

Farbe: Blau; Größe: 66 x 114 cm / VE: 8STK

---

**pure<sup>11</sup> GmbH**

Bavariafilmplatz 7 | D-82031 Grünwald

Geschäftsführung: Julian Kropp, Linda Vereycken, Lars Engeler

AG München HRB 171307

T +49 89 5589434 0

F +49 89 5589434 77

[www.pure11.de](http://www.pure11.de)

[info@pure11.de](mailto:info@pure11.de)

## Sticky Mat CELOS<sup>®</sup>

### Product information:

<i>Material</i>	Polyethylene
<i>Application</i>	For particle control and risk reduction in cleanrooms and controlled environments
<i>Color</i>	Blue
<i>Thickness</i>	1.5 mm

### Product:

<i>Part number</i>	<i>Color</i>	<i>Size</i>	<i>Inner packing</i>	<i>Quantity per case</i>
<b>1108041</b>	Blue	66 x 114 cm	30 layers/mat	8 mats/case
<i>Parallel part number</i> <b>08041</b>	<i>Please note: The packaging may show either of the parallel valid part numbers during the changeover period.</i>			

### Characteristics:

- Extreme high stability and adhesion
- Solid single layer due to foil thickness
- Consistent grip strength
- Layers/foils with index numbering
- Antimicrobial
- Easy usage on all surfaces
- Production and packaging in a controlled environment

### Performance parameter:

	<i>Specification</i>	<i>Unit</i>
Adhesive after aging	450 (+/- 30)	g/mm
Back adhesive strength	200 (+/-30)	g/mm
Bottom adhesive strength	700 (+/-30)	g/mm
Heat resistance	60	°C/48h
Cold resistance	-1	°C/48h

Based on research and testing, pure<sup>11</sup> can recommend the usage of the sticky mat in cleanrooms up to ISO 4, according to ISO 14644-1.

pure<sup>11</sup> has made every attempt to ensure the accuracy and reliability of the information provided in this datasheet. However, the information is provided "as is" without warranty of any kind. pure<sup>11</sup> does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained.

## Sticky Mat L30-8 CELOS<sup>®</sup>

### Product information:

<i>Material</i>	Polyethylene
<i>Application</i>	For particle control and risk reduction in cleanrooms and controlled environments
<i>Color</i>	Blue
<i>Thickness</i>	1.5 mm

### Product:

<i>Part number</i>	<i>Color</i>	<i>Style</i>	<i>Size</i>	<i>Inner packaging</i>	<i>Quantity per case</i>
<b>1108041</b>	Blue	Non-sterile	66 x 114 cm	30 layers/mat	8 mats/case
<i>Parallel part number</i> <b>08041</b>	<i>Please note: The packaging may show either of the parallel valid part numbers during the changeover period.</i>				

### Characteristics:

- Extreme high stability and adhesion
- Solid single layer due to foil thickness
- Consistent grip strength
- Layers/foils with index numbering
- Antimicrobial
- Easy usage on all surfaces
- Production and packaging in a controlled environment

### Performance parameter:

	<i>Specification</i>	<i>Unit</i>
Adhesive after aging	450 (+/- 30)	g/25mm
Back adhesive strength	200 (+/-30)	g/25mm
Bottom adhesive strength	700 (+/-30)	g/25mm
Heat resistance	60	°C/48h
Cold resistance	-1	°C/48h

Based on research and testing, pure<sup>11</sup> can recommend the usage of the sticky mat in cleanrooms up to ISO 4, according to ISO 14644-1.

pure<sup>11</sup> has made every attempt to ensure the accuracy and reliability of the information provided in this datasheet. However, the information is provided "as is" without warranty of any kind. pure<sup>11</sup> does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained.