

TexWipe



## Tuch AlphaLite #TX1008B

pure<sup>11</sup>-Nr.: 1106004, Marke: TexWipe

### Eigenschaften

- Marke: TexWipe
- Flächengewicht in g/m<sup>2</sup>: 121 g/m<sup>2</sup>
- Struktur: Gestrick
- Material: Polyester
- Lieferform in Verpackung: geschüttet (bulk)
- Verpackungsform: Beutel
- Anzahl in kleinster Unterverpackung: 75
- Autoklavierbar
- Kantenverarbeitung: Kalt geschnitten
- Gebrauch: Einweg
- Polyester/PES: 100 %
- Vorgewaschen
- Flächengewicht in g/m<sup>2</sup>: 121 g/m<sup>2</sup>

### Empfohlene

### Reinraumklassen

ISO 5|6|7|8|9

GMP C|D



## Material

- Polyester

## Verpackung

- 150STK

## Produktvarianten

---

**pure<sup>11</sup>-Nr.: 1106004, Tuch AlphaLite #TX1008B**

Größe: 23 x 23 cm (9 x 9"); Farbe: Weiß / VE: 150STK

---

TECHNICAL DATA SHEET

**Performance Characteristics**

Property	Typical Value	Test Method*
<b>Particles and Fibers</b> LPC: ≥ 0.5 µm Fibers: >100 µm	14 x 10 <sup>6</sup> particles/m <sup>2</sup> 1,400 fibers/m <sup>2</sup>	1, TM22 2, TM22
<b>Nonvolatile Residue</b> IPA extractant DIW extractant	0.05 g/m <sup>2</sup> 0.01 g/m <sup>2</sup>	1, TM1 1, TM1
<b>Ions</b> Sodium Potassium Chloride	0.20 ppm 0.10 ppm 0.10 ppm	1, TM18 1, TM18 1, TM18

**Physical Characteristics**

Property	Typical Value	Test Method*
<b>Absorbency</b> Sorptive capacity Sorptive rate	350 mL/m <sup>2</sup> 0.5 seconds	1, TM20 1, TM20
<b>Basis Weight</b>	121 g/m <sup>2</sup>	1, TM20

**\*Test Methods**

- 1 – “Evaluating Wiping Materials Used in Cleanroom and Other Controlled Environments,” IEST-RP-CC004.3, Institute for Environmental Sciences and Technology, Rolling Meadows, IL, 2004; [www.iest.org](http://www.iest.org).
- 2 – E2090-12, “Standard Test Method for Size-Differentiated Counting of Particles and Fibers Released from Cleanroom Wipers Using Optical and Scanning Electron Microscopy,” ASTM International, West Conshohocken, PA, 2012; [www.astm.org](http://www.astm.org).
- TM – Refers to Texwipe Test Method – available upon request. Contact Texwipe Customer Service at [www.texwipe.com](http://www.texwipe.com) or [info@texwipe.com](mailto:info@texwipe.com) for a copy.

Note: The data in this table represent typical analyses.

*Texwipe holds ISO 9001 and ISO 14001 registrations.*

*All Texwipe products conform to GHS classification for labeling (where applicable).*

*Shipping classification based on weight of inner package.*

# AlphaLite®

## Dry Wipers

TEX-LIT-TDS-006 Rev.00-02/17

TECHNICAL DATA SHEET



AlphaLite®  
100% polyester

### Products

Number	Description	Sterile	Packaging	Case
<i>Dry Wipers – AlphaLite®</i>				
<b>TX1008</b>	9" x 9" (23 cm x 23 cm) dry		150 wipers/bag (2 inner bags of 75)	10 bags
<b>TX1008B</b>	9" x 9" (23 cm x 23 cm) dry, bulk packaged		150 wipers/bag (2 inner bags of 75)	10 bags

TECHNICAL DATA SHEET

### Description

AlphaLite® is made from 100% polyester with a cut edge, cleanroom laundered.

Available dry (AlphaLite®).

### Applications

- Wiping and cleaning surfaces, equipment and parts.
- Applying and removing lubricants, adhesives, residues and other solutions including disinfectants.
- Cleaning with solvents such as isopropyl alcohol (IPA), ethanol, acetone, and degreasers.
- Cleaning gloves, notebooks, phones or any other item entering the cleanroom.
- Lining trays for holding, protecting, drying and storing of parts, equipment and devices.
- Appropriate for use with temperatures less than 400°F (205°C).

### Industries

Aerospace	Animal Laboratory	Biologics
Cleanroom Design/Build	Compounding Pharmacies	Data Storage
Facilities Maintenance	Industrial	Laboratory
Medical Device	Microelectronics	Pharmaceutical
Printing/Graphics	Semiconductor	USP <797> / USP <800>

### Features & Benefits

- Constructed from 100% polyester creating a wiper ideal for spill control, cleaning, and solution application.
- Cleanroom laundered providing low levels of ions and NVRs (non-volatile residues) particles.
- Designed for use on abrasive surfaces. This wiper will not easily snag or abrade releasing particles and fibers into the process or environment.
- Excellent chemical resistance for compatibility with a variety of solutions.
- Meets USP <797> and USP <800> wiper requirements.
- Autoclave safe.
- Individually lot coded for ease of traceability and quality control.

### Cleanroom Environment

- ISO Class 4 – 8
- Class 10 – 100,000
- EU Grade A – D

### Shelf Life

- Non-Sterile (Dry) – 5 years from date of manufacture