

UltraTape

Reinraum-Klebeband laminiertes Vinyl #1186-3

pure¹¹-Nr.: 1130138, Marke: UltraTape

Eigenschaften

- Marke: UltraTape
- Material: Vinyl
- Breite in cm: 7,62 cm
- Anzahl in kleinster Unterverpackung: 2
- Klebestärke: stark
- Klebstoff: Acryl
- Reinheitsgrad: Ultra Clean
- Vinyl: 100 %

Empfohlene

Reinraumklassen

ISO 4|5|6|7|8|9

GMP C|D

Material

- Vinyl

Verpackung

- 2STK

Produktvarianten

pure¹¹-Nr.: 1130138WH3I, Reinraum-Klebeband laminiertes Vinyl #1186-3

Farbe: Weiß; Breite: 3 Inches / VE: 2STK

pure¹¹-Nr.: 1130138YL3I, Reinraum-Klebeband laminiertes Vinyl #1186-3

Farbe: Gelb; Breite: 3 Inches / VE: 2STK

UT1186 Solid Color Over Laminated Floor Marking Cleanroom Tape

DESCRIPTION

UltraTape 1186/ 0186 tape is a polished polymeric flexible calendered vinyl with permanent acrylic pressure sensitive adhesive, over laminated with a 1.0 mil clear biaxially-oriented polyester.

- Comes in a variety of colors
- Water Resistant
- Extremely durable
- Adheres well to all surfaces

PROPERTIES

Backing	Calendered Vinyl
Adhesive	Acrylic
Release Liner	Kraft
Backing Thickness	4.4 mils (0.1118 mm) with O/L
Adhesive Thickness	1.0 mil (0.025mm)
Adhesion to Stainless Steel	40 oz/in. (1.14 kg/25mm)
Operating Temperature	-10°F to 200°F (-23°C to 93°C)
Minimum Application Temperature	40°F
Length	18 yards
Colors	Black (BK), Blue (BL), Green (GR), Orange (OR), Red (RE), White (WH), Yellow (YE)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.