

Klebefolienmatte L30-8 CELOS

pure11-Nr.: 1108041, Marke: CELOS

Eigenschaften

- Marke: CELOS
- Breite in cm: 66 cm
- Länge in cm: 114 cm
- Dicke/Stärke der Matte (in mm): 1,5 mm
- Anzahl Lagen: 30
- Abnehmende Indexnummerierung
- Klebestärke: stark
- Farbe: Blau
- Farbe der einzelnen Klebefolien: Blau

Empfohlene Reinraumklassen

ISO 4 | 5 | 6 | 7 | 8 | 9

GMP C | D

we care

pure11 GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

Material

-

Verpackung

- 8STK

Produktvarianten

pure[11]-Nr.: 1108041, Klebefolienmatte L30-8 CELOS

Farbe: Blau; Größe: 66 x 114 cm / VE: 8STK

pure[11] GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

CELOS®
a pure[11] brand

Sticky Mat L30-8 CELOS®

Product information:

Material	Polyethylene
Application	For particle control and risk reduction in cleanrooms and controlled environments
Color	Blue
Thickness	0.040 mm (± 0.003 mm)

Product:

Part number	*Color*	*Style*	*Size*	*Inner packaging*	*Quantity per case*
1108041	Blue	Non-sterile	66 x 114 cm	30 layers/mat	8 mats/case
Parallel part number 08041	*Please note: The packaging may show either of the parallel valid part numbers during the changeover period.*				

Characteristics:

- Extreme high stability and adhesion
- Solid single layer due to foil thickness
- Consistent grip strength
- Layers/foils with index numbering
- Easy usage on all surfaces
- Production and packaging in a controlled environment

Performance parameter:

	Typical tested value	*Unit*
Adhesive after aging	450 (+/- 50)	g/25mm
Back adhesive strength	300 (+/-50)	g/25mm
Bottom adhesive strength	700 (+/-50)	g/25mm
Tensile Strength	Over 150	kgf/10 mm^2
Elongation	Over 250	%
Heat resistance	70 (+/- 3)	°C/48h
Cold resistance	-13 (+/- 3)	°C/48h
Weatherability	200	Hr

Based on research and testing, pure[11] can recommend the usage of the sticky mat in cleanrooms up to ISO 4, according to ISO 14644-1.

pure[11] has made every attempt to ensure the accuracy and reliability of the information provided in this datasheet. However, the information is provided "as is" without warranty of any kind. pure[11] does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained.

pure11 GmbH | Sitz: Grünwald
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

we care