

Paxxo



## LONGOPAC Maxi Bag Strong #10296

pure<sup>11</sup>-Nr.: 1113391, Marke: Paxxo

### Eigenschaften

- Material Packmittel & Entsorgungsbeutel: Polyethylen
- Durchmesser in mm: 570 mm
- Farbe: Blau
- Folienstärke in µm: 35 µm
- Länge Schlauchfolie in m: 90 m
- LONGOPAC Folienstärke: Strong
- Passend für System: LONGOPAC Maxi
- Marke: Paxxo

### Empfohlene

### Reinraumklassen

ISO 5|6|7|8|9

GMP C|D

## Material

- 

## Verpackung

- STK

## Produktvarianten

---

**pure<sup>11</sup>-Nr.: 1113391MAXIBL, LONGOPAC Maxi Bag Strong #10296**

Passend für Longostand Maxi / VE: STK

---

**pure<sup>11</sup>-Nr.: 1113391MAXIBK, LONGOPAC Maxi Bag Strong #10291**

Passend für Longostand Maxi / VE: STK

---

**pure<sup>11</sup>-Nr.: 1113391MAXIRD, LONGOPAC Maxi Bag Strong #10292**

Modell: Maxi; Farbe: Rot / VE: STK

---

**pure<sup>11</sup>-Nr.: 1113391MAXITP, LONGOPAC Maxi Bag Strong #10290**

Passend für Longostand Maxi / VE: STK

---



## Product data sheet

### Longopac Maxi

**Application:** Unique endless waste bag system which allows the user to continuously make their own bags. This gives substantial advantages in handling and low transport costs.

#### Specifications

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| <b>Material</b>          | 3-layer coextruded polyethylene (PE).                      |
| <b>Size of Packaging</b> | 1 pc per box. 395x225x140mm.                               |
| <b>Weight</b>            | Cassette only: 4,6 kg. Included with box: 4,95 kg (+/-0,2) |
| <b>Diameter</b>          | 570 mm                                                     |
| <b>Color</b>             | Transparent, black, blue, red, yellow and green            |
| <b>Others</b>            | The material is SVHC free                                  |

|               | <b>Dart Drop*<br/>Guaranteed</b> | <b>Initial</b> | <b>Length</b> | <b>Thickness</b> | <b>CO<sup>2</sup><br/>reduction**</b> | <b>Oil<br/>reduction***</b> |
|---------------|----------------------------------|----------------|---------------|------------------|---------------------------------------|-----------------------------|
| Maxi ECO      | 450g                             |                | 125m          | 22µm/0,9mil      |                                       |                             |
| Maxi Standard | 510g                             |                | 110m          | 25µm/1,0mil      | 12-18 kg                              | 6-9 liters                  |
| Maxi Strong   | 700g                             |                | 90m           | 32µm/1,3mil      |                                       |                             |
| Maxi X-Strong | 820g                             |                | 70m           | 45µm/1.8mil      |                                       |                             |

\*Dart Drop is measured according to ASTM D-1709. The value is the guaranteed value average end of shelf life. See link for more information

<http://www.astm.org/Standards/D1709.htm>

\*\*Based on Longopac LCA. Lower value is estimated reduction when replacing 40µm 125 liter recycled bag and higher value is for a 60µm 160 liter bag.

\*\*\*1 liter oil is about 2 kg CO<sup>2</sup>.

#### Tensile Strength

| <b>MD/TD</b> | <b>Parameter</b>          | <b>Unit</b> | <b>Maxi Standard</b> | <b>Maxi Strong</b> |
|--------------|---------------------------|-------------|----------------------|--------------------|
| MD           | Tensile Strength at break | MPa         | 24                   | 29                 |
| TD           | Tensile Strength at break | MPa         | 25                   | 27                 |

#### Tear Resistance Strength

| <b>MD/TD</b> | <b>Parameter</b> | <b>Unit</b> | <b>Maxi Standard</b> | <b>Maxi Strong</b> |
|--------------|------------------|-------------|----------------------|--------------------|
| MD           | Tear Resistance  | N           | 1,7                  | 1,8                |
| TD           | Tear Resistance  | N           | 4,6                  | 6,1                |





## Product data sheet

### Longopac Maxi

#### Disposal

Complete incineration of polyethylene yields nothing but water, carbon dioxide (CO<sub>2</sub>) and energy.

#### Storage

Shelf life is guaranteed for 2 years.

Storage conditions: Indoor (protect from UV light and sun light)

Storage temperature (-10°C) – (+50°C)

#### Quality Management systems

PAXXO's quality system is certified in accordance with ISO 9001 and our environmental management system is certified in accordance with ISO 14001.

#### Reach Compliance

1. PAXXO has secured that our suppliers have pre-registered the chemical substances during 2012 that occur in our products (dependent on volume) and that are subject to registration with the European Chemical Authority (ECHA) in accordance with REACH.
2. None of the articles supplied contain substances under Annex XIV of REACH or the candidate list (SVHC – substances).



**PAXXO AB** • Bjurögatan 35 • SE-211 24 MALMÖ • SWEDEN  
TEL +46 (0)40 186025 • FAX +46 (0)40 183736  
**PAXXO Inc** • 1924 Millard Farmer Road • GA. 30263 • Newnan • USA  
TEL +1 770 502 0055 • FAX +1 770 502 0088  
[www.paxxo.com](http://www.paxxo.com) • E-mail: [info@paxxo.com](mailto:info@paxxo.com)