

pure[11]-Nr.: 1130046, Marke:

Eigenschaften

Empfohlene Reinraumklassen

ISO

GMP

we care

pure[11] GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

Material

-

Verpackung

- Box

Produktvarianten

pure¹¹-Nr.: 1130046,

pure¹¹-Nr.: 1130046WH2I, Reinraum-Klebeband Polyolefin High Purity #1164-2

Farbe: Weiß; Breite: 2'' / VE: 3STK

pure¹¹ GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

UltraTape
Adhesive Tape & Labels for Critical Environments

PRODUCT DATASHEET

UT1164 Polyolefin Medium Adhesion Cleanroom Tape

DESCRIPTION

UltraTape 1164/ 0164 is a single coated tape consisting of a polypropylene film coated with a specially formulated acrylic adhesive system.

- Ultra low outgassing
- No residue
- Low sulfur, low halogen and low heavy metal
- Cleanroom certified

PROPERTIES

Backing	Polyolefin Polypropylene
Adhesive	Acrylic
Elongation	100%
Backing Thickness	3.5 mils /.0889mm
Adhesive Thickness	1.1 mil /.028mm
Adhesion to Stainless	35 oz/in (9.73 N/25.4mm)
Operating Temperature	-40°F to 190°F (-40°C to 87°C)
Tensile Strength	30 lbs./in (130 N/25.4mm)
Length	60 yards
Colors	White (WH)

To achieve ultimate adhesion, the bonding surface should be clean, dry, and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly in contact with the adhesive. Firm pressure is recommended to achieve good adhesive to surface contact.

UltraTape recommends that each user conduct their own test to determine the product's suitability for the intended application and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21C°) with 50% relative humidity.

9770 SW Wilsonville Road, Suite 400
Wilsonville, OR 97070
www.cleanroomtape.com

503.427.2880
503.482.5616

© UltraTape 2022 | Rev. 05/2022

ISO 9001:2015

UL LISTED

A division of DELPHON