Tiger-Vac

Empfohlene Reinraumklassen

ISO 4 | 5 | 6 | 7 | 8 | 9

GMP C | D

Staubsauger #CWR-8 (Poly) #110499B

pure[11]-Nr.: 1111103, Marke: Tiger-Vac

Eigenschaften

- Marke: Tiger-Vac
- Art Staubsauger: Naß-/Trockensauger
- Tuchfilter
- ULPA-Filter
- DUAL-ULPAFilter
- Filtrationssystem: 5-stufig
- Filterbeutel
- Stromspannung: 240 V
- Stromstärke in A: 5 A
- Gewicht in kg: 11 kg
- Alleinstellungsmerkmal: EMI/RFI-geschirmt
- Behälterkapazität in L (nass): 24,6 L
- Behälterkapazität in L (trocken): 24,6 L
- Breite in cm: 43 cm
- Filterbeutelkapazität in L: 9,5 L
- Geräuschentwicklung in dB(A): 75 dB(A)
- Höhe in cm: 74 cm
- Leistung in Watt: 1.050 W
- Luftstrom in m³/h: 189 m³/h

- Material Gehäuse: Edelstahl / Polyethlylen-Tank
- Motor: Einphasiger Bypass-Motor
- Netzkabel Länge in cm: 1.006 cm
- Netzkabel Typ: European Plug

Material

-

Verpackung

- STK

Produktvarianten

pure¹¹-Nr.: 1111103, Staubsauger #CWR-8 (Poly) #110499B

Naß-/Trockensauger / VE: STK

pure¹¹ GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

Tiger-Vac®
...The name to vacuum with

CWR POLY SERIES
Pharma - Wet & Dry Recovery

Characteristics



Pharma Applications | Cleanroom Compatible | Wet and Dry Recovery | ULPA - Included | High Filtration Efficiency Unit | Activated Carbon

Accessories Included | EMI Shielded

- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- EMI/RFI Shielded
- 5-stage filtration system, includes dual ULPA filters (U15) (one for the working air and one for the cooling air), double cloth filter, and disposable filter bags
- Available with a Middle Ring with Activated Carbon (MRAC) for the adsorption of toxic/noxious fumes and vapors
- Designed for use in contamination controlled environments
- Heavy duty 2-stage by-pass motor
- For wet & dry recovery
- Polyethylene recovery tank with polished metal powerhead
- Mounted on a 4-wheel dolly for easy maneuverability
- Includes a complete tool kit.

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu
Email: info@tiger-vac.it

Specifications

CWR POLY SERIES	110498B	110498C	110498D	110498E	110499B	110499C
Model Name	CWR-15 (4W) POLY	CWR-15 (4W) POLY	CWR-15 (4W) POLY	CWR-15 (4W) POLY	CWR-8 POLY	CWR-8 POLY
Type (Powerhead)	Electric	Electric	Electric	Electric	Electric	Electric
Tension	240 V	240 V	240 V	240 V	240 V	240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single	Single	Single
Wattage	1050 W	1050 W	1050 W	1050 W	1050 W	1050 W
Power	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
Amperage	5 A	5 A	5 A	5 A	5 A	5 A
Air Flow	189 m^3/h	189 m^3/h	189 m^3/h	189 m^3/h	189 m^3/h	189 m^3/h
Vacuum Pressure	2180 mm H_20	2180 mm H_20	2180 mm H_20	2180 mm H_20	2180 mm H_20	2180 mm H_20
Sound Level	75 dB(A)	75 dB(A)	75 dB(A)	75 dB(A)	75 dB(A)	75 dB(A)
Type of Power Outlet	European	UK	Swiss	Chinese	European	UK
Suction Inlet	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None	None	None	None	None
Dust Recovery Tank	47.3 L	47.3 L	47.3 L	47.3 L	24.6 L	24.6 L
Dry Recovery - Disposable Filter Bag	19 L	19 L	19 L	19 L	9.5 L	9.5 L
Liquid Recovery Capacity	47.3 L	47.3 L	47.3 L	47.3 L	24.6 L	24.6 L
Cord Length	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m

CWR POLY SERIES	110499D	110499E
Model Name	CWR-8 POLY	CWR-8 POLY
Type (Powerhead)	Electric	Electric
Tension	240 V	240 V
Frequency	50 Hz	50 Hz
Phase	Single	Single
Wattage	1050 W	1050 W
Power	1 kW	1 kW
Amperage	5 A	5 A
Air Flow	189 m^3/h	189 m^3/h
Vacuum Pressure	2180 mm H_20	2180 mm H_20
Sound Level	75 dB(A)	75 dB(A)
Type of Power Outlet	Swiss	Chinese
Suction Inlet	38 mm	38 mm

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu
Email: info@tiger-vac.it

Cart Type	4 Wheel Dolly (4W)	4 Wheel Dolly (4W)
Filter Cleaning	None	None
Dust Recovery Tank	24.6 L	24.6 L
Dry Recovery - Disposable Filter Bag	9.5 L	9.5 L
Liquid Recovery Capacity	24.6 L	24.6 L
Cord Length	10.6 m	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories

CWR-8 Poly Tank

ULPA Filter - Included

CWR Tools and Accessories - Included



CWR Tools and Accessories - Optional

Needle Trap - Optional

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu
Email: info@tiger-vac.it

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: http://www.tiger-vac.eu
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: http://www.tiger-vac.com
Email: sales@tiger-vac.com

Pharma Applications

Cleanroom Compatible

Wet and Dry Recovery

ULPA - Included

High Filtration Efficiency Unit

Activated Carbon

Accessories Included


EMI Shielded

Specifications For CWR POLY SERIES

Name	Part Number	Tension	Frequency	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Type of Power Outlet	Dust Recovery Tank	Dry Recovery - Disposable Filter Bag
CWR-15 (4W) POLY	**110498B**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	European	47.3 L	19 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-15 (4W) POLY	**110498C**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	UK	47.3 L	19 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-15 (4W) POLY	**110498D**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	Swiss	47.3 L	19 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-15 (4W) POLY	**110498E**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	Chinese	47.3 L	19 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-8 POLY	**110499B**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	European	24.6 L	9.5 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-8 POLY	**110499C**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	UK	24.6 L	9.5 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												
CWR-8 POLY	**110499D**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	Swiss	24.6 L	9.5 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												

CWR-8 POLY	**110499E**	240 V	50 Hz	Single	1050 W	1 kW	5 A	189 m^3/h	2180 mm H_20	Chinese	24.6 L	9.5 L
	Sound Level: 75 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.												

Please note that specifications are subject to change without notice

Technical Sheet For CWR POLY SERIES

ULPA FILTER AND ACCESSORIES - Included	
Part #	**Description**
211027	ULPA FILTER (U15)

FILTERS AND ACCESSORIES FOR MODEL CWR-8 POLY - Included	
Part #	**Description**
211265	DOUBLE CLOTH FILTER ASSEMBLY
211274	LIQUID FILTER FILTER ASSEMBLY

FILTERS AND ACCESSORIES FOR MODEL CWR-15 POLY - Included	
Part #	**Description**
211305A	DOUBLE CLOTH FILTER ASSEMBLY WITH LACES FOR STAINLESS STEEL FILTER CAGE (CAGE SOLD SEPARATELY)
212734A	STAINLESS STEEL CAGE FOR CLOTH FILTER -ELECTROPOLISHED

DISPOSABLE FILTER BAGS FOR MODEL CWR-8 POLY - Included	
Part #	**Description**
219028-5	SYNTHETIC RECOVERY BAGS (WHITE) FOR EMI CWR (PACKAGE OF 5)
212731	PVC PIPE CONNECTOR FOR PAPER FILTER BAG(WITH 4 CRIMPS TO FIT ELBOW)

DISPOSABLE FILTER BAGS FOR MODEL CWR-15 POLY - Included	
Part #	**Description**
218063-5	SYNTHETIC RECOVERY BAGS, 10" x 28", 50mm COLLAR (PACKAGE OF 5))
211845	PVC PIPE CONNECTOR FOR PAPER FILTER BAG FOR CWR-15 POLY TANK & MRV-15 (WITH 4 CRIMPS TO FIT ELBOW)

DRAIN HOSE FOR MODEL CWR-15 POLY - Included	
Part #	**Description**
381092	DRAIN HOSE ASSEMBLY 0.75"(19mm)x5'(1.5m)CLEAR HOSE WITH 0.75"(19mm) PVC FEMALE CAMLOCK

TOOLS AND ACCESSORIES - Included	
Part #	**Description**
323404	SUCTION HOSE ASSEMBLY,1.25"(32mm)x10'(3m)CLEAR URETHANE, ITH SS CURVED HANDLE&PLASTIC FEMALE CAMLOCK
323330	EXTENSION WANDS, BOTH STRAIGHT, 1.25"(32mm) x 20.5"(52cm), STAINLESS STEEL (SET OF 2)
323311	COMBI TOOL, 1.25"(32mm) x 10.5" (27cm), BEIGE, WITH HOLE FOR BUTTON LOCK
323317	UTILITY FLOOR TOOL WITH WHEELS & WITH SQUEEGEE BLADES 1.25"(32mm) x 12"(30cm), BEIGE PLASTIC
323321	ROUND TOOL, WITH RUBBER BLADES, Ø1.25"(32mm)
323314	UPHOLSTERY FLAT TOOL, Ø1.25"(32mm), PVC
323313	CREVICE TOOL, 1.25"(32mm) x 9"(23cm), BEIG, PVC
211701	DEFOAMING LIQUID (BOTTLE) 909 ml(31 fl oz.)- FOR WET RECOVERY MODE ONLY

TOOLS AND ACCESSORIES - Optional	
Part #	**Description**
323470	FOODGRADE HOSE ASSEMBLY 1.25"(32mm)x10'(3m) FOR CWR-XX (SMOOTH INSIDE & OUT)
323455	EPDM HOSE ASSEMBLY SD* AUTOCLAVABLE 1.25" x 10' (32mm x3m) w/1.5" s/S SWIVEL CAMLOCK & CURVED HANDLE
323412	FLOOR TOOL ASSEMBLY, AUTOCLAVABLE, 1.25"(32mm) x 12"(30cm), STAINLESS STEEL w/WHITE NITRILE BLADES
323413	CREVICE TOOL, AUTOCLAVABLE, Ø1.25"(32mm)x10"(25.4cm) -STAINLESS STEEL

NEEDLE TRAP AND ACCESSORIES - Optional	
Part #	**Description**
215500	NEEDLE TRAP ASSEMBLY, STAINLESS STEEL, 2"(50mm) INLET X 1.25"(32mm) OUTLET, ELECTROPOLISHED
500235M	TIGER-CLAW ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x4.5"(11.5cm)
500231M	CONICAL NOZZLE ONLY (TRANSPARENT FOODGRADE SILICONE) Ø2"(50mm)x7.5"(19cm)