Tiger-Vac

Empfohlene Reinraumklassen

ISO 4 | 5 | 6 | 7 | 8 | 9

GMP C | D

Staubsauger #MV-1CR (HH)

pure[11]-Nr.: 1111201, Marke: Tiger-Vac

Eigenschaften

- Marke: Tiger-Vac
- Art Staubsauger: Hand-/Tragegerät
- Antistatisch
- ESD-Eigenschaften
- Tuchfilter
- ULPA-Filter
- Filtrationssystem: 4-stufig
- Filterbeutel
- Stromspannung: 240 V
- Stromstärke in A: 4 A
- Gewicht in kg: 6 kg
- Alleinstellungsmerkmal: EMI/RFI-geschirmt
- Behälterkapazität in L (trocken): 2 L
- Breite in cm: 20 cm
- Filterbeutelkapazität in L: 1,9 L
- Geräuschentwicklung in dB(A): 64 dB(A)
- Höhe in cm: 20 cm
- Kuppelfilter
- Länge in cm: 53 cm

we care

pure[11] GmbH |
Bavariafilmplatz 7 | D-82031 Grünwald
T +49 89 5589434 0
F +49 89 5589434 77
www.pure11.de
info@pure11.de

- Leistung in Watt: 750 W
- Luftstrom in m³/h: 198 m³/h
- Material Gehäuse: Edelstahl
- Motor: Einphasiger Durchfluss-Motor
- Netzkabel Länge in cm: 1.006 cm
- Netzkabel Typ: European Plug

Material

-

Verpackung

- STK

Produktvarianten

pure¹¹-Nr.: 1111201, Staubsauger #MV-1CR (HH)

Trockensauger, Hand-/Tragegerät / VE: STK

Tiger-Vac®
...The name to vacuum with

MV-1CR (HH)
Pharma - Dry Recovery Only

Characteristics



ULPA - Included | High Filtration Efficiency Unit | Cleanroom Compatible | Pharma Applications | Static Dissipating | Less than 10 ohms

Dry Recovery | SS 304 | SD Accessories - Included | EMI Shielded

- ULPA filter with an efficiency of 99.999% at 0.12 micron. Filtration efficiency of 99.9995% at 0.18 micron. Tested IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- Static free and ESD safe
- EMI/RFI Shielded
- 4-stage filtration system, includes an ULPA filter (U15), cloth filter, dome filter, and a disposable filter bag
- Special filter lined with stainless steel is available for the recovery of broken wafers and sharp objects
- Designed for use in contamination controlled environments
- Thru-Flow heavy duty motor
- For dry recovery only
- All stainless steel Type 304 construction
- Shoulder strap set available
- Includes a complete tool kit.

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu
Email: info@tiger-vac.it

Specifications

MV-1CR (HH)	110735B	110735C	110735D	110735E
Model Name	MV-1CR (HH) WITH EUROPEAN PLUG	MV-1CR (HH) WITH UK PLUG	MV-1CR (HH) WITH SWISS PLUG	MV-1CR (HH) WITH CHINESE PLUG
Type (Powerhead)	Electric	Electric	Electric	Electric
Tension	240 V	240 V	240 V	240 V
Frequency	50 Hz	50 Hz	50 Hz	50 Hz
Phase	Single	Single	Single	Single
Wattage	1000 W	1000 W	1000 W	1000 W
Power	1 kW	1 kW	1 kW	1 kW
Amperage	4.2 A	4.2 A	4.2 A	4.2 A
Air Flow	187 m^3/h	187 m^3/h	187 m^3/h	187 m^3/h
Vacuum Pressure	1750 mm H_20	1750 mm H_20	1750 mm H_20	1750 mm H_20
Sound Level	70 dB(A)	70 dB(A)	70 dB(A)	70 dB(A)
Suction Inlet	38 mm	38 mm	38 mm	38 mm
Cart Type	Hand Held (HH)	Hand Held (HH)	Hand Held (HH)	Hand Held (HH)
Filter Cleaning	None	None	None	None
Dry Recovery - Disposable Filter Bag	1.9 L	1.9 L	1.9 L	1.9 L
Length	23 cm	23 cm	23 cm	23 cm
Width	23 cm	23 cm	23 cm	23 cm
Height	53 cm	53 cm	53 cm	53 cm
Weight (Vacuum Only)	6 kg.	6 kg.	6 kg.	6 kg.
Cord Length	10.6 m	10.6 m	10.6 m	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories

ULPA filter for MV-1CR (HH) - individually laser tested

MV-1CR Tools and Accessories - Optional

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)

Website: http://www.tiger-vac.eu
Email: info@tiger-vac.it