



## Klebefolienmatte L30-8 CELOS

pure<sup>11</sup>-Nr.: 08040, Hersteller: CELOS

### Zusammenfassung

- Klebekraft: stark
- Anzahl Lagen: 30
- 30 weiße Lagen pro Matte
- Mattengrundlage: Weiß
- Dicke/Stärke der Matte: 1,5 mm
- Besonders hohe Stabilität und Adhäsion
- Robuste Einzellagen durch erhöhte Folienstärke
- Gleichbleibende Klebekraft mit jeder Lage und Produktionscharge
- Antimikrobiell ausgerüstet
- Schichten/Folien mit abnehmender Indexnummerierung

### Empfohlene Reinraumklassen

ISO	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
GMP	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

### Produktvarianten

pure<sup>11</sup>-Nr.: 08040W

Farbe: Weiß / Maße: 66 x 114 cm / Herst.-Nr.: 08040W / VE: 8 Stück

Quelle: <https://www.pure11.de/klebefolienmatte-l30-8-celos>

## Sticky Mat CELOS®

### Product information:

<i>Material</i>	Polyethylen
<i>Application</i>	For particle control and risk reduction in cleanrooms and controlled environments
<i>Color</i>	White or Blue, depending on model
<i>Thickness</i>	1.5 mm

### Products:

<i>Part number</i>	<i>Color</i>	<i>Size</i>	<i>Inner packing</i>	<i>Quantity per case</i>
<b>08040</b>	White	66 x 114 cm	30 layers/mat	8 mats/case
<b>08041</b>	Blue	66 x 114 cm	30 layers/mat	8 mats/case

### Characteristics:

- Extreme high stability and adhesion
- Solid single layer due to foil thickness
- Consistent grip strength
- Layers/foils with index numbering
- Antimicrobial
- Easy usage on all surfaces
- Production and packaging in a controlled environment

### Performance parameter:

	<i>Specification</i>	<i>Unit</i>
Adhesive after aging	450 (+/- 30)	g/mm
Back adhesive strength	200 (+/-30)	g/mm
Bottom adhesive strength	700 (+/-30)	g/mm
Heat resistance	60	°C/48h
Cold resistance	-1	°C/48h

pure<sup>11</sup> has made every attempt to ensure the accuracy and reliability of the information provided in this datasheet. However, the information is provided "as is" without warranty of any kind. pure<sup>11</sup> does not accept any responsibility or liability for the accuracy, content, completeness, legality, or reliability of the information contained.